# Door Tablet ABX
## Wayfinding Signage - For Common Areas

**DOOR TABLET**

## A compact device for Door Tablet Wayfinding displays for public areas and touch kiosks



### Easy to Install
Works "out of the box" with the Door Tablet system. Enables Wayfinding displays, welcome messaging and screensavers to be seen in your communal areas.

### Remote Management
Manage the Door Tablet ABX remotely using the Door Tablet Web UI.

### Interactive or Read-Only
Use with the Door Tablet touch and non-touch displays for read-only or interactive Wayfinding.

### Full HD and Multi-Screen
HDMI output ensures a crystal-clear display (up to 1920 x 1080 dpi) and clarity of text. Connect to multiple screens using an HDMI splitter.

### Slim, Hardened Design
Fits easily behind all displays using the supplied velcro fittings. A robust device that will survive knocks and bangs.

### Wired Ethernet or Wi-Fi
Clean installation via a single cable, with IEEE 802.3 standard. Wi-Fi connectivity also available, if desired.

### eMMC Storage
Reliable read/write data settings ensure existing data will not be corrupted when a sudden power loss occurs.

### Environmentally Friendly
Shut down automatically for nights and weekends to conserve power, helping the environment and saving money too.

## Features

| | |
|---|---|
| CPU | ARM quad-core 1.6GHz |
| Memory | 2GB DDR3 |
| Storage | 8GB eMMC |
| Orientation display | Landscape/Portrait |
| Audio codecs | MP3 |
| Networking+ | Wired and Wi-Fi |

## Operating Environment

| | |
|---|---|
| Type | Android 5.1 |
| HDMI Output Resolution | Up to 1920 x 1080 |
| RTC | Supported |
| Watchdog Timer | Supported |

## I/O Interface

| | |
|---|---|
| Ethernet | RJ45 (10M/100M) |
| USB | 3x USB2.0 type / Micro USB |
| Analog Stereo out | 1 x S/PDIF |
| Expansion storage | Micro SDHC slot |

## Mechanical

| | |
|---|---|
| Dimensions | 154.2 x 143.6 x 37.8 mm (6.07" x 5.65" x 1.49") |
| Weight | 514g |
| Mounting | Surface / Scotched |
| Housing | Metallic |
| Environment | Operating Temp. 0~50°C Storage Temp. -20°C to 60°C Humidity: 10 to 85% |
| Power | DC 12V, 1.5A |
| Certification | CE/FCC |

http://door-tablet.com   |   sales@door-tablet.com
UK +44 800 910 1131  |  USA +1 407 545 5925

Server is available for download after registration
Tablet apps are available from Apple, Google and Microsoft Application stores.
**Search:** door tablet

**DOOR TABLET**

Door Tablet is a trademark of Public. Class Limited. All other trademarks belong to their respective owners.

ABX_2.6 20191219