

Door Tablet SL

Workspace Signage Touch Display



Our slim, streamlined, purpose-built display is placed outside your meeting spaces



Easy to Install

Works “out of the box” and comes with all the fixtures and fittings needed. It’s easy to mount on any surface including glass, brick and metal. The device comes with a security lock, built-in.



Readable at Wide Viewing Angles

The IPS display ensures the screen can be read comfortably at a distance and at wide angles so there’s no need to get up close to read what’s being displayed.



Sturdy

The screen is tempered glass which means it is tough, easy to clean and will not shatter, crack or deteriorate excessively with time or heavy use. It’s built to last and stay looking good.



Attractive

It is sleek and slim (2.1cm deep) with a 10.1” high resolution (1280 x 800 dpi) full color touchscreen so the display is easy to read and provides smooth interaction. Add your branding and make the device yours.




Power over Ethernet (PoE+) Built-in

With no need to rely on Wi-Fi signals, a single PoE cable powers the SL, giving you the important benefit of full power management to save costs and the environment. Shut down and restart screens as needed.



LED Light on Front

A bright and colorful LED light strip on the front of the Door Tablet SL signals that a room is free or busy and is visible from distance - so there is no need to walk up to a room to see its status. Use the SL with the LED strip at the top or bottom of the device.



Features

CPU	ARM quad-core 1.5GHz
Memory	2GB DDR3L
Storage	16GB eMMC
Orientation display	Landscape/Portrait
Audio codecs	MPEG/OGG/ACC
Colors	Black
PoE/PoE+	Yes

Display

Size	10.1"
Max resolution	1280 x 800
Brightness	350 nits
Contrast ratio	1000 : 1
Viewing angles	170h/170v

I/O Interface

Ethernet	RJ45; 10M/100M
USB	2x USB2.0 type A
Analog Stereo out	3.5mm stereo
Expansion storage	Micro SDHC slot
Speaker	2W x 2

Mechanical

Dimensions without stand	248 x 166 x 20.8mm 9.76" x 6.54" x 0.82"
Weight	615g / 1.375 lbs
Mounting	Glass / Surface
Housing	Plastic
Environment	Operating Temp. 0~50°C Humidity: 10 to 90% non-condensing
Power	PoE
Certification	CE/FCC/RoHS/NCC/IMDA

<https://door-tablet.com> | sales@door-tablet.com

UK: +44 800 910 1131 | USA: +1 407 545 5925

Server and Door Tablet software are available for download after registration

Tablet Apps are available from Apple, Google and Microsoft stores.

Search: door tablet

Door Tablet is a trademark of Public.Class Limited. All other trademarks belong to their respective owners.

